

Multimatic Air Star Hybrid Class

Designed for environmentally friendly solvents!



Dual Cleaning Method

- * **Full Immersion**
- * **Spray Jet**



- * No Water Necessary
- * Lower Your Utility Costs
- * Can Be Used With or Without Steam
- * 2 Separate Filter Systems
- * High Efficiency Air Cooling System
- * No Distillation Required
- * Refrigerated Solvent Cooling (Air Cooled Models)
- * Stainless Steel Construction
- * Simple, Easy Installation
- * Exclusive Multimatic MultiComp III Computer



Multimatic

162 Veterans Drive, Northvale, NJ 07647/USA
Telephone 201-767-9660 • Fax: 201-767-7037

SPECIFICATIONS

Multimatic AirStar

| MODEL | AS40 | AS65 |
|---|--------------|----------------|
| BASKET | | |
| Capacity (lbs. Maximum) | 40 | 65 |
| Volume, cu. ft. | 12.5 | 22 |
| Diameter, in. | 37.5 | 44 |
| Depth, in. | 19.5 | 26 |
| Cleaning Speed, rpm | 40 | 34 |
| Extraction Speed | 575 | 550 |
| TANKS | | |
| Work Tank I (gallons) | 57 | 84 |
| Work Tank II (gallons) | 57 | 84 |
| FILTER* | | |
| Cartridges (split) | 6 | 12 |
| MACHINE DIMENSIONS | | |
| Width, in. | 77.2 | 89 |
| Depth, in. | 54 | 72 |
| Height, in. | 90 | 95.5 |
| Machine with Tray, in. | 79 x 59 x 94 | 91 x 75 x 99.5 |
| <i>Partially dismantled for clearance</i> | | |
| Depth x Height, in. | 49 x 79 | 62 x 84 |
| FLOOR LOAD | | |
| Weight, lbs. (without solvent) | 2203 | 4846 |
| POWER REQUIREMENTS, STEAM HEATED | | |
| Max. Operating Load, amps | 40 | 50 |
| Motor | | |
| Drive, HP | 5 | 10 |
| Solvent Pump, HP | 1 | 1.5 |
| Drying Fan, High Speed HP | 3.4 | 3.4 |
| Refrigeration Compressor, HP | 5.0 | 8.0 |
| SUPPLY CONNECTIONS | | |
| Compressed Air | | |
| Pressure, psi | 85-95 | 85-95 |
| Size of Fitting, in. | 1/4 | 1/4 |
| Steam (Where used to provide most efficient operation) | | |
| Pressure, psi | 45-60 | 45-60 |
| Size of Fitting, in. | | |
| Steam Inlet | 1/2 | 1/2 |
| Condensate Return | 1/2 | 1/2 |
| Water Required on water-cooled models | | |
| Pressure, psi | 45-85 | 45-85 |
| Size of Fitting, in. | | |
| Water Inlet | 1 | 1 |
| Water Outlet | 1 | 1 |
| ELECTRICAL REQUIREMENT | | |
| | 208-220/60/3 | 208-220/60/3 |
| All Specifications Subject to Change Without Notice *Available with either spin disc or cartridge filtration | | |

RIB-MAY 2009



Multimatic

162 Veterans Drive, Northvale, NJ 07647/USA
Telephone: 201-767-9660 • Fax: 201-767-7037